



4900 SLIDING HI

TBB

ENERGY EFFICIENCY

Thermal Transmission Coefficient
 $U_w \geq 1.2$ (W/m²K)

Please consult typology, dimensions and glazing

ACCOUSTIC INSULATION

Maximum glazing: **36 mm**
Maximum acoustic insulation: **Rw = 40 dB**

CATEGORIES ACHIEVED AT TEST CENTRE

Protection against atmospheric agents

Air permeability (EN 12207): **Class 4**
Water tightness (EN 12208): **Class 7A**
Wind resistance (EN 12210): **Class C5**

Reference test 1.23 x 2.48 m / 2 sashes

SECTIONS	60, 70, 89, 120, 125, 130 mm 126, 145 mm 3 rails 201 mm 4 rails	EXTRUSION ALLOY	6063 T-5
PROFILE THICKNESS	Window 1.6 mm	POLYAMIDE STRIP LENGTH	34 mm
MAXIMUM DIMENSIONS	Width (L) = 2.200 mm Height (H) = 2.600 mm	OPENING POSSIBILITIES	Sliding Possibility of 1, 2, 3 & 4 rails Possibility of galandage
MAXIMUM WEIGHT/SASH	240 Kg	AVIS TECHNIQUE CERTIFICATE	DTA certification from CSTB lab 
FINISHES	Colour powder coating (RAL, mottled, rough...) According to Qualicoat >60 microns Wood effect powder coating According to Qualideco standard Anodized According to Ewwa Euras Standard Class 15 Optionally Class 20 and 25 Optionally bicoloured		

Please consult regarding maximum weight and dimensions according to types

